Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

- (Currently Amended) A service cartridge for removable positioning in a filter housing for use; the service cartridge, prior to installation in the filter housing, comprising:
 - filter media having first and second ends and positioned around a central open area;
 - (b) a first end cap secured to the first end of the filter media; and,
 - the first end cap being a closed end cap with no aperture therethrough; and.
 - a treatment agent storage and release cartridge secured to the second end of the media;
 - the treatment agent storage and release cartridge having a ring configuration defining an inside wall defining a central flow conduit in liquid flow communication with the central open area defined by the filter media;
 - (A) the inside wall having no diffusion apertures therethrough;
 and,
 - the treatment agent storage and release cartridge also having an outer sidewall and an end wall remote from the filter media;
 - (A) the end wall having a flow aperture arrangement therethrough;
 - the outer sidewall having a flow aperture arrangement therethrough; and,
 - (C) a total diffusion area of the flow aperture arrangement in the outer sidewall being greater than a total diffusion area of the flow aperture arrangement in the end wall; and,

- a housing seal arrangement comprising a radially inwardly directed seal member positioned on the treatment agent storage and release cartridge and oriented to releasably seal to a central housing standpipe when the cartridge is installed in a housing, for use;
- (e) the filter media having no impermeable wall there around in extension completely between the first and second ends of the filter media, when the cartridge is ready for installation in a filter housing, for use.

2. (Cancelled)

3. (Cancelled)

- 4. (Previously Presented) A filter cartridge according to claim 1 wherein:
 - the treatment agent storage and release cartridge comprises a cup having a cover;
 - the filter media being secured to the cover with adhesive.
- 5. (Original) A filter cartridge according to claim 4 including:
 - a mounting prong arrangement projecting axially outwardly from the first end cap.
- 6. (Original) A filter cartridge according to claim 5 wherein:
 - (a) the media is pleated media.
- 7. (Original) A filter cartridge according to claim 6 wherein:
 - (a) the cartridge includes no cylindrical media support liner.
- 8. (Original) A filter cartridge according to claim 7 wherein:
 - an axial length ratio of the filter media to the treatment agent storage and release cartridge is at least 1.5.

- 9. (Original) A filter cartridge according to claim 7 wherein:
 - an axial length ratio of the filter media to the treatment agent storage and release cartridge is at least 2.0.
- 10. (Original) A filter cartridge according to claim 9 wherein:
 - the axial length ratio of the filter media to the treatment agent storage and release cartridge is within the range of 2.2 to 3.0.
- 11. (Original) A filter cartridge according to claim 10 wherein:
 - (a) the first end cap is a closed end cap.
- 12-17. Previously Cancelled